

CEWELD Ceramic Backing strip Ø shaped

TYPE Ceramic backing Round

APPLICATIONS This ceramic backing strip offer special economic advantages for submerged arc welding and MAG welding with solid wires or metal- cored wires in the downhand position as well for positional MAG welding using rutile cored wires with fast freezing slag.

PROPRIÉTÉS Available in the dimensions:

| Ø (mm) | Longueur (mm) |
|--------|---------------|
| 6 | 600 |
| 8 | 600 |
| 10 | 600 |
| 12 | 600 |
| 15 | 600 |

CLASSIFICATION

CONVIENT POUR one side welding with high currents in shipbuilding, pressure vessel fabrication, machine construction, crane building, tank, and general steel building.

AGRÉMENTS


POSITIONS DE SOUDAGE



PROPRIÉTÉS MÉCANIQUES

ETUVAGE Not required

GAS ACC. EN ISO 14175



CEWELD Ceramic Backing strip Ø shaped

| | | | |
|---------------------------------------|-----------|-------------------|---------------|
| CERAMIC BACKING STRIP Ø SHAPED Ø 10MM | Packaging | KG/unit | EanCode |
| | 0,6 | 60 meters per box | 8720663410856 |
| CERAMIC BACKING STRIP Ø SHAPED Ø 12MM | Packaging | KG/unit | EanCode |
| | 0,6 | 54 meters per box | 8720663410863 |
| CERAMIC BACKING STRIP Ø SHAPED Ø 15MM | Packaging | KG/unit | EanCode |
| | 0,6 | 42 meters per box | 8720663410870 |
| CERAMIC BACKING STRIP Ø SHAPED Ø 6MM | Packaging | KG/unit | EanCode |
| | 0,6 | 90 meters per box | 8720663410832 |
| CERAMIC BACKING STRIP Ø SHAPED Ø 8MM | Packaging | KG/unit | EanCode |
| | 0,6 | 72 meters per box | 8720663410849 |