


# CEWELD Alu-Flux

|                       |                                                                                                                                         |             |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------|
| TYPE                  | Flux for aluminium brazing                                                                                                              |             |
| TOEPASSINGEN          | Alu-Fux is for brazing from Aluminium and Aluminium Alloys with a working range from 350 to 550 °C                                      |             |
| EIGENSCHAPPEN         | Usually combined with AlSi12 or AlSi5 filler metal.                                                                                     |             |
| CLASSIFICATIE         | EN ISO                                                                                                                                  | 18496: FL20 |
| GESCHIKT VOOR         | Brazing for Aluminium and Aluminium Alloys with a working range from 350 to 550 °C. Usually combined with AlSi12 or AlSi5 filler metal. |             |
| GOEDKEURINGEN         |                                                                                                                                         |             |
| LASPOSITIES           |                                                                                                                                         |             |
| MECHANISCHE WAARDEN   |                                                                                                                                         |             |
| HERDROGEN             | Not required                                                                                                                            |             |
| GAS ACC. EN ISO 14175 |                                                                                                                                         |             |



# CEWELD Alu-Flux

ALU-FLUX NAMM

| Packaging | KG/unit | EanCode       |
|-----------|---------|---------------|
| Jar       | 0,25    | 8720663423016 |